



# n5™ Video Server Technical Specification

## Specifications

---

### Physical

Operating Temperature °F (°C)	41 °F to 95 °F / 5 °C to 35 °C
Operating Relative Humidity (Min-Max)	5% to 85%, non-condensing
Storage Temperature °F (°C)	-40 °F to 158 °F / -40 °C to 70 °C
Color	BLACK
Dimensions (H x W x D) inches	8.63 x 17.5 x 26.25
Depth (front to rear) inches	27.66
Weight lbs (kg)	No power supplies; no drives: 80 lbs 2 power supplies; no drives: 98 lbs 2 power supplies; 24 disk drives: 134 lbs

---

### Electrical Specifications

Input Voltage	90-256Vac RMS, 10 A, max.
Frequency	47-63 Hz
Power Source Phasing	Single-phase
Power Cord (harmonized)	IEC 320, 12 ft. (4 m)

---

### Power Consumption

Power Consumption	730 W
Heat Dissipation	2492BTU (hour)

---

### Certifications and Regulations

Safety Certification	UL, cUL Mark, CE Mark
EMC Certification	FCC Class A, CE Mark
Meets or exceeds the following requirements:	
Safety Regulations	IEC60950, UL/CSA60950, EN60950
RFI/EMI	FCC Class A Pt. 15, EN55022, CISPR 22
Immunity	EN 55024, EN/IEC 61000-4-2, 3, 4, 5, 6, 8, 11

---

# Technical Specification

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice®, C3™, C4®, C4c™, Cadant®, C-COR®, CHP Max™, CHP Max5000™, ConvergeMedia™, Cornerstone®, CORWave™, CXM™, D5®, Digicon®, ENCORE®, Flex Max®, HEMI®, Keystone™, MONARCH®, MOXI®, n5®, nABLE®, nVision®, OpsLogic®, OpsLogic® Service Visibility Portal™, PLEXIS®, PowerSense™, QUARTET™, Regal®, ServAssure™, Service Visibility Portal™, TeleWire Supply®, TLX®, Touchstone®, EGT VIPR®, VoiceAssure™, VSM™, and WorkAssure™ are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2010 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.